

Material Safety Data Sheet**Product: 1570**

Printing date 10/09/2006

Reviewed on 10/09/2006

1 Identification of substance









- **Product details**
- **Trade name:** **Salami Pack Urethane Sealant/Adhesive (Sausage Pack)**
- **Article number:** 1570
- **Application of the substance / the preparation :** Polyurethane-sealant
- **Manufacturer/Supplier:**
International Epoxies & Sealers
30241 Commerce Drive
San Antonio, FL 33576
Telephone: 1-800-451-7206

Emergency Information: INFOTRAC: 1-800-535-5053
Outside the U.S. Call Collect: 1-352-323-3500

2 Composition/Data on components

- **Chemical characterization**
- **Description:**
Product containing a polyurethane prepolymer based on diphenylmethanediisocyanate.

• **Dangerous components:**

1330-20-7	xylene, mixture of isomers	 Xn,  Xi; R 10-20/21-38	2-5%
1305-78-8	calcium oxide	 Xi; R 41	< 2.5%
64742-47-8	Distillates (petroleum), hydrotreated light	 Xn; R 65-66	< 2.5%
100-41-4	ethylbenzene	 Xn,  F; R 11-20	< 2.5%
101-68-8	diphenylmethane-4,4'-diisocyanate	 Xn,  Xi; R 20-36/37/38-42/43	< 1%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- **Hazard description:**



Xn Harmful

- **Information pertaining to particular dangers for man and environment:**

R 42 May cause sensitization by inhalation.

Contains isocyanates. See information supplied by the manufacturer.

- **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- **NFPA ratings (scale 0 - 4)**



Health = 0
Fire = 2
Reactivity = 0

- **WHMIS-ratings (scale 0 - 4)**



Health = 0
Fire = 2
Reactivity = 0

USA

(Contd. on page 2)

Material Safety Data Sheet**Product: 1570**

Printing date 10/09/2006

Reviewed on 10/09/2006

Product: 1570

(Contd. of page 1)

4 First aid measures

- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **The following symptoms may occur:**
Dizziness
Headache
Dizziness
Nausea

5 Fire fighting measures

- **Suitable extinguishing agents:**
Carbon dioxide
Foam
Fire-extinguishing powder
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards caused by the material, its products of combustion or resulting gases:**
In case of fire, the following can be released:
Carbon monoxide (CO)
Nitrogen oxides (NOx)
In certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:
Hydrogen cyanide (HCN)
Isocyanates
- **Protective equipment:** Wear self-contained respiratory protective device.

6 Accidental release measures

- **Person-related safety precautions:**
Ensure adequate ventilation
Keep away from ignition sources
- **Measures for environmental protection:**
Do not allow product to reach sewage system or any water course.
- **Measures for cleaning/collecting:**
Pick up mechanically.
Send for recovery or disposal in suitable receptacles.
Do not close them (reaction with water forming carbon dioxide)

7 Handling and storage

- **Handling:**
- **Information for safe handling:** Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Provide ventilation for receptacles.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in dry conditions.

(Contd. on page 3)

USA

Material Safety Data Sheet

Product: 1570

Printing date 10/09/2006

Reviewed on 10/09/2006

Product: 1570

(Contd. of page 2)

Store in a cool place.

8 Exposure controls and personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Components with limit values that require monitoring at the workplace:**

1330-20-7 xylene, mixture of isomers

PEL	435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

1305-78-8 calcium oxide

PEL	5 mg/m ³
REL	2 mg/m ³
TLV	2 mg/m ³

64742-47-8 Distillates (petroleum), hydrotreated light

TLV	Short-term value: 1 200 mg/m ³ , 165 ppm
-----	---

100-41-4 ethylbenzene

PEL	435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 543 mg/m ³ , 125 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

101-68-8 diphenylmethane-4,4'-diisocyanate

PEL	Short-term value: C 0.2 mg/m ³ , C 0.02 ppm
REL	Short-term value: C 0.2* mg/m ³ , C 0.02* ppm Long-term value: 0.05 mg/m ³ , 0.005 ppm *10-min
TLV	0.051 mg/m ³ , 0.005 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Avoid close or long term contact with the skin.

Wash hands before breaks and at the end of work.

Do not eat, drink or smoke while working.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Short term filter device:

Filter AB

· **Protection of hands:**

PVA gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Eye protection:** Tightly sealed goggles

· **Body protection:** Protective work clothing

USA

(Contd. on page 4)

Material Safety Data Sheet**Product: 1570**

Printing date 10/09/2006

Reviewed on 10/09/2006

Product: 1570

(Contd. of page 3)

9 Physical and chemical properties**· General Information**

Form: Pasty
Color: Various colors
Odor: Light

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 137°C (279°F)

· Flash point: 40-55°C (104-131°F)

· Flammability (solid, gaseous): The product is not subject to classification because its speed of combustion is lower than the limit of the regulation.

· Ignition temperature: >200°C (>392°F)

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower: 0.6 Vol %
Upper: 7 Vol %

· Density at 20°C (68°F): 1.17

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

10 Stability and reactivity**· Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

· Materials to be avoided:**· Dangerous reactions**

Reacts with alcohols, amines, aqueous acids and alkalis.

Reacts with water forming carbon dioxide. Danger of receptacles bursting because of vapour overpressure.

· Dangerous products of decomposition: No dangerous decomposition products known.

11 Toxicological information**· Acute toxicity:****· LD/LC50 values that are relevant for classification:****1330-20-7 xylene, mixture of isomers**

Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
Inhalative	LC50/4 h	6350 mg/l (rat)

100-41-4 ethylbenzene

Oral	LD50	3500 mg/kg (rat)
Dermal	LD50	17800 mg/kg (rbt)

· Primary irritant effect:

· on the skin: May be slightly irritant.

· on the eye: Light irritating effect.

· Sensitization: Sensitization possible through inhalation.

USA

(Contd. on page 5)

Material Safety Data Sheet**Product: 1570**

Printing date 10/09/2006

Reviewed on 10/09/2006

Product: 1570

(Contd. of page 4)

12 Ecological information

- **Ecotoxicological effects:**
- **Other information:** -
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow product to reach ground water, water course or sewage system.

13 Disposal considerations

- **Product:**
- **Recommendation:**
Must be disposed of in an incinerator for hazardous waste according to official regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **DOT regulations:**
- **Hazard class:** -
- **Remarks:** Not hazardous
- **Land transport ADR/RID (cross-border):**
- **ADR/RID class:** -
- **Remarks:** Not hazardous
- **Maritime transport IMDG:**
- **IMDG Class:** -
- **Marine pollutant:** No
- **Remarks:** Not hazardous
- **Air transport ICAO-TI and IATA-DGR:**
- **ICAO/IATA Class:** -
- **Proper shipping name:** Not regulated
- **Remarks:** Not hazardous.

15 Regulations· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene, mixture of isomers

100-41-4 ethylbenzene

101-68-8 diphenylmethane-4,4'-diisocyanate

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**· **Chemicals known to cause cancer:**

100-41-4 ethylbenzene

1333-86-4 Carbon black

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

(Contd. on page 6)

Material Safety Data Sheet**Product: 1570**

Printing date 10/09/2006

Reviewed on 10/09/2006

Product: 1570

(Contd. of page 5)

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Cancerogenity categories**

- **EPA (Environmental Protection Agency)**

1330-20-7	xylene, mixture of isomers	D
100-41-4	ethylbenzene	D
101-68-8	diphenylmethane-4,4'-diisocyanate	CBD;D

- **IARC (International Agency for Research on Cancer)**

9002-86-2	Polyvinyl chloride	3
1330-20-7	xylene, mixture of isomers	3
100-41-4	ethylbenzene	2B
1309-37-1	diiron trioxide	3
1333-86-4	Carbon black	2B
101-68-8	diphenylmethane-4,4'-diisocyanate	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene, mixture of isomers	A4
1309-37-1	diiron trioxide	A4
1333-86-4	Carbon black	A4
77-58-7	dibutyltin dilaurate	A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black
-----------	--------------

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

- **Product related hazard informations:**

The product has been classified and marked in accordance with EU Directives.

- **Hazard symbols:**

Xn Harmful

- **Hazard-determining components of labelling:**

diphenylmethane-4,4'-diisocyanate

- **Risk phrases:**

42 May cause sensitization by inhalation.

- **Safety phrases:**

45 In case of accident or if you feel unwell, seek medical advice immediately.

- **Special labeling of certain preparations:**

Contains isocyanates. See information supplied by the manufacturer.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.