

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 08/23/2007

Reviewed on 08/23/2007

1 Identification of substance

Trade name: GREEN PHOSPHATE PRIMER

Part Number: 4530

Manufacturer/Supplier: Intrenational Epoxies & Sealers
P.O. Box 185
San Antonio, FL
(800) 451-7206

Information department: Health & Safety Department

Emergency information: INFOTRAC 1-800-535-5053, 1-352-323-3500 Call Collect if located outside the U.S.

2 Composition/Data on components

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	33.02%
74-98-6	propane	15.73%
106-97-8	n-butane	9.24%
108-88-3	Toluene	8.37%
110-19-0	isobutyl acetate	4.36%
64-17-5	ethyl alcohol	4.3%
1330-20-7	xylene (mix)	3.55%
64742-89-8	VM&P Naptha	1.73%
64742-47-8	Mineral Spirits	1.42%
1314-13-2	zinc oxide	0.21%

Additional information: For the wording of the listed risk phrases refer to section 3.

3 Hazards identification

Hazard description:



Harmful
Extremely flammable

Physical dangers:

Extremely flammable liquid and vapor in a pressurized container. Keep away from heat, sparks, and flame.
Extremely flammable.
Irritating to eyes.
Possible risk of harm to the unborn child
Keep out of the reach of children.

Effects of short-term overexposure:

Vapors cause irritation to the eyes, nose, throat, skin, and central nervous system. Symptoms may include dizziness, throat irritation, headache, fatigue, swelling of eyes, and nausea.

Effects of chronic overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

NFPA ratings (scale 0 - 4):

Health = 1
Fire = 4
Reactivity = 3

HMIS-ratings (scale 0 - 4):

Health= 1
Fire= 4
Physical Hazard= 3

4 First aid measures

After inhalation:

Supply fresh air; consult doctor in case of complaints.

After skin contact:

Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact:

Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Contact physician or poison control center.

5 Fire fighting measures

Extinguishing agents:

CO₂, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 2)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 08/23/2007

Reviewed on 08/23/2007

Trade name: GREEN PHOSPHATE PRIMER
Protective equipment: No special measures required.

(Contd. of page 1)

6 Accidental release measures

Personal safety
precautions:

Wear protective equipment. Keep unprotected persons away.

Environmental safety
precautions:

 Inform appropriate authorities in case of seepage into water course or sewage system.
 Do not allow product to reach sewage systems or ground water.

**Measures for cleaning/
collecting:**

Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up spills with inert absorbent material. Refer to section 13 for disposal information.

7 Handling and storage

Fire/explosion protection: Do not spray on a naked flame or any incandescent material.

Do not smoke. Protect from electrostatic charges.

Storage requirements:

Observe pressurized container storage regulations. Consult with your local authorities.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

8 Exposure controls and personal protection:

Components with limit values that require monitoring at the workplace:
67-64-1 Acetone

 PEL 2400 mg/m³, 1000 ppm

 REL 590 mg/m³, 250 ppm

 TLV Short-term value: 1782 mg/m³, 750 ppm

 Long-term value: 1188 mg/m³, 500 ppm

BEI

106-97-8 n-butane

 REL 1900 mg/m³, 800 ppm

108-88-3 Toluene

PEL Short-term value: C 300; 500* ppm

Long-term value: 200 ppm

*10-min peak per 8-hr shift

 REL Short-term value: 560 mg/m³, 150 ppm

 Long-term value: 375 mg/m³, 100 ppm

 TLV (188) NIC-75 mg/m³, (50) NIC-20 ppm

(Skin); (BEI)

110-19-0 isobutyl acetate

 PEL 700 mg/m³, 150 ppm

 REL 700 mg/m³, 150 ppm

 TLV 713 mg/m³, 150 ppm

64-17-5 ethyl alcohol

 PEL 1900 mg/m³, 1000 ppm

 REL 1900 mg/m³, 1000 ppm

 TLV 1880 mg/m³, 1000 ppm

1330-20-7 xylene (mix)

 PEL 435 mg/m³, 100 ppm

 REL Short-term value: 655 mg/m³, 150 ppm

 Long-term value: 435 mg/m³, 100 ppm

 TLV Short-term value: 651 mg/m³, 150 ppm

 Long-term value: 434 mg/m³, 100 ppm

BEI

Protective hygienic
measures:

Keep away from foodstuffs and animal feed. Wash hands after use.

Breathing equipment:

Use suitable respiratory protective device in case of insufficient ventilation.

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases of inadequate ventilation, a respiratory protective device should be worn to prevent overexposure.

Protection of hands:

Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.

(Contd. on page 3)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 08/23/2007

Reviewed on 08/23/2007

Trade name: GREEN PHOSPHATE PRIMER

Eye protection: Tightly sealed goggles

(Contd. of page 2)

9 Physical and chemical properties:

General Information:

Form: Aerosol
Color: According to trade name description in section 1.
Odor: Solvent
Boiling point/Boiling range: -44°C (-47°F)

Flash point: -19°C (-2°F)

Ignition temperature: 365.0°C (689°F)

Auto igniting: Product is not self-igniting.

Danger of explosion: Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit.
In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol %

Upper Explosion Limit: 10.9 Vol %

Vapor Pressure: 40 PSI, 2750 hPa

Density: Not determined.

Specific Gravity: Between 0.77 and 0.85 (Water equals 1.00)

VOC content: 866.3 g/l / 7.23 lb/gl

VOC in weight percent (less acetone): 50.5 %

Solids content: 16.2 %

10 Stability and reactivity:

Conditions to be avoided: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.

Possibility of Hazardous

Reactions: No dangerous reactions known.

11 Toxicological information:

Primary effect on the skin: No irritant effect.

Primary effect on the eye: Irritating effect.

Sensitization: No sensitizing effects known.

Additional toxicological information: Harmful

12 Ecological information

Other information: This product does not contain any chloroflourocarbons (CFC's),chlorinated solvents, lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyl (PBB), or polybrominated diphenyl ether (PDBE). No specific ecological data is available for this product.

13 Disposal considerations

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Empty cans should be recycled.

14 Transport information:

Hazard class: 2.1
Identification number: N/A
Label: 2.1
ADR/RID class: 2 5TF Gases
UN-Number: 1950
IMDG Class: 2
Packaging group: II
EMS Number: F-D,S-U
Marine pollutant: No

(Contd. on page 4)

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 08/23/2007

Reviewed on 08/23/2007

Trade name: GREEN PHOSPHATE PRIMER

(Contd. of page 3)

ICAO/IATA Class: 2.1
Propper shipping name: Aerosols, Flammable
Consumer Commodity ORM-D

15 Regulations

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

1330-20-7 xylene (mix)

TSCA (Toxic Substances

Control Act): All ingredients are listed.

PROPOSITION 65 Chemicals known to cause cancer:

100-41-4 ethyl benzene

1333-86-4 Carbon black

PROPOSITION 65

Chemicals known to cause developmental toxicity:

108-88-3 Toluene

Canadian WHMIS: Class A, B5---Flammable Aerosols

EPA: A= Known human carcinogen B= Probable human carcinogen

C= Possible human carcinogen

D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).

110-19-0	isobutyl acetate	D
1330-20-7	xylene (mix)	D

IARC: Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.
Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

1330-20-7	xylene (mix)	3
-----------	--------------	---

ACGIH TLVs: A1-designates a confirmed human carcinogen.
A2-designates a suspected human carcinogen.
A3-designates an animal carcinogen.
A4-designates "not classifiable as a human carcinogen".

110-19-0	isobutyl acetate	A4
64-17-5	ethyl alcohol	A4
1330-20-7	xylene (mix)	A4

NIOSH:

1333-86-4	Carbon black
-----------	--------------

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.