

IES 1000 RESTORE-IT

A unique cleaner and protector that has been formulated to remove compound and white haze from textured plastic, door handles and fender flares. *RESTORE-IT* also leaves a long lasting dressing without silicone. Restores old faded mouldings and cladding.

RESTORE-IT also restores old faded side mouldings. For example: replace a door moulding and the quarter panel moulding looks faded next to it. Use *RESTORE-IT* to bring back that lost color! Needs 1 hour dry/cure time to be water-proof.

BENEFITS

- Cleans & Renews Faded Trim
- Instantly Removes Embedded Wax & Compound From Textured Body Side Mouldings
- Restores Color
- Beautifies
- Protects
- No Silicone Contaminates!

APPLICATIONS

- Perfect for Body Shops - Silicone Free
- Any Color Rubber & Vinyl
- Textured & Smooth Surfaces
- Plastic
- Headlight Lens Restoration!
- Vinyl Tops
- Painted Trim
- Mouldings
- Weather Stripping
- Door Handles
- Wipers
- Mud Flaps
- Tires

anything plastic or rubber that needs restoring!

STORAGE

Product should be stored in a cool, dry location in unopened containers at a temperature between 46°F to 82°F (8°C to 28°C) unless otherwise labeled. Optimal storage is at the lower half of this temperature range. To prevent contamination of unused material, do not return any material to its original container.



DIRECTIONS

1. SHAKE WELL BEFORE AND DURING USE. Apply sparingly to a clean cloth.
2. Apply to a cool, dry exterior surface only. Do not apply in direct sunlight or on a hot surface.
3. IMPORTANT: Run in with a back and forth motion (not circular). Run until cloth becomes dirty (until compound, wax or oxidation is removed) and until luster is restored. Turn to clean part of cloth and repeat procedure on next area. NOTE: Will not harm paint finish and easily wipes off of paint surface with a soft, clean, dry cloth.
4. Allow to dry - buffing with a soft, dry cloth will improve some textured surfaces. Some especially faded or dirty surfaces may require a repeat application.
5. IMPORTANT: To achieve maximum results, AFTER APPLYING, place vehicle in direct contact with the rays of the sun. DO NOT OPERATE VEHICLE IN RAIN UNTIL TREATED SURFACE IS COMPLETELY DRY. Allow 30-60 minutes drying time in damp conditions.
6. On vinyl tops: Slightly moisten cloth with water before application, then buff top with clean, soft, dry cloth.

PRODUCT AVAILABLE

1000 8 fl. oz. (236ml) bottle 12 per case

These suggestions and data are based on information we believe to be reliable and accurate, but no guarantee of their accuracy is made. International Epoxies & Sealers shall not be liable for any damage, loss or injury, direct or consequential arising out of the use or the inability to use the product. In every case, we urge and recommend that purchasers, before using any product in full scale production, make their own tests to determine whether the product is of satisfactory quality and suitability for their operations, and the user assumes all risk and liability whatsoever, in connection therewith.