



BRAKE SILENCER

Specifically formulated to help prevent brake squeal on brake systems. IES Brake Silencer soaks into pad surface to fill voids and pits. Reduces combacks and improves customer satisfaction.

Eliminates Pad Squeal

Fills Voids & Pits On Pad Surface

Reduces Side Pull

Will Not Affect Life Of Pad

DIRECTIONS:

1. Mix well before using.
2. Clean brake pad with IES Brake Cleaner
3. If pad is glazed, use emory cloth or sand paper to remove glaze.
4. Clean again with IES Brake Cleaner and allow to dry.
5. Appl IES Brake Silencer to surface of pad.
6. When first coat has soaked into pad surface and is dry, apply a second coat.
7. Allow to dry before reassembly.

NOTE: Drying time can be accelerated by warming the back plate of the brake pad with a heat gun prior to the application of IES Brake Silencer.

TESTING BRAKES:

Drive in a forward motion at 10 mph and make 5 or 6 panic stops.
Then drive in reverse at 10 mph and make 2 or 3 panic stops.
Drive forward again at 30 mph and make 2 or 3 regular stops.

NOTE: For the first two or three stops, the brakes will grab and groan.
This is normal. By the fifth or sixth stop the brakes should return to normal.

Product # 1450
8 oz. Bush Top Can
Packaged 12 per case