

## ***FLEXIBLE PRIMER SURFACER***



Flexible Primer Surfacers is designed specifically for priming and filling plastic, TPO, urethane and fiberglass parts. Can also be used on metal autobody parts.

**Professional Fan Spray**

**Fast Drying**

**Flexible**

**Super Adhesion**

**Easy Sanding**

**Excellent Filling And Feathering Ability**

### **DIRECTIONS:**

1. Surface must be clean, dry and free of rust before painting. Use IES #1700 or #4700 Super Clean to remove any contaminants from surface.
2. Shake can for 1 minute after mixing ball moves freely.
3. Feather edge and sand painted surfaces. Do not use over newly painted surfaces.
4. Spray surface with steady, even strokes at a distance of 6 to 8 inches. Longer distances may cause poor hide and Poor adhesion. Allow primer to dry 10 to 20 minutes before recoating or top coating.
5. Lightly sand primer with fine sandpaper before top coating.
6. When finished, turn can upside down and spray about 3 seconds to clean out valve and sprayhead.

NOTE: Sprayhead provides a horizontal and vertical fan spray by turning the nozzle clockwise or counterclockwise.

NOTE: When painting plastic parts, we recommend using IES #4182 Adhesion Promoter.

**Product # 4185**  
**20 oz. Size Aerosol Can**  
**Net Weight 15 oz.**  
**Packaged 12 per case**

NOTICE TO PURCHASER: The following warranty is in lieu of all other expressed or implied warranties, specifically all goods are manufactured of first class materials and by competent professionals. We have no control over the use and application of our products. Our liability shall not exceed the purchase price.