



IESTM **SELF ETCHING** **PRIMER (GREEN)**

This primer chemically etches the surface of bare metal to replace the "metal conditioning" step on bare metal. May be used for the repair of small rub-throughs to bare metal or the complete coating of new panels.

Professional Fan Spray

Dries Fast

Excellent Adhesion

Corrosion Resistant

No Measuring, Mixing or Gun Cleaning!

Chemically Etches To Bare Metal

Easy To Use

DIRECTIONS:

1. Surface must be clean, dry and free of rust before painting. Use IES #1700 or #4700 Super Clean to remove any contaminants from surface.
2. Shake can for 1 minute after mixing ball moves freely.
3. Feather edge and sand painted surfaces. Do not use over newly painted surfaces.
4. Apply 2 to 3 medium coats allowing a 3 to 5 minute dry time between each coat. Spray surface with steady, even strokes at a distance of 6 to 8 inches. Longer distances may cause poor hide and poor adhesion. Product will be dry to the touch in 15 minutes. **Allow one hour dry time** before sanding, priming or top-coating. No need to sand if re-coated within 24 hours.
6. When finished, turn can upside down and spray about 3 seconds to clean out valve and sprayhead.

NOTE: Sprayhead provides a horizontal and vertical fan spray by turning the nozzle clockwise or counterclockwise.

Product # 4186
20 oz. Size Aerosol Can
Net Weight 14 oz.
Packaged 12 per case