

INTER-SKIM

Flowable Polyester Glazing Putty

INTER-SKIM is a two part, flowable polyester glazing putty, ideal for final finishing over body filler, paint, pinholes, scratched and rust pits. Each bottle comes with a 1 oz. tube of hardener.

Superior Adhesion

Great Feather Edging

Easy To Sand

No Pin Holes

DIRECTIONS:

- Preparation:** Clean surface with *IES Super Clean* to remove all dirt, waxes, grease, grime and any other contaminants. Sand surface with 180 grit sand paper and then wipe down again with *IES Super Clean* and allow to dry.
- Mixing:** Shake *INTER-SKIM Polyester Putty* well before using. Puncture inner seal and then dispense desired amount of *INTER-SKIM Putty* on a clean, non porous, mixing board. Knead the *INTER-SKIM Hardener* tube to insure contents are well mixed. Apply a ribbon of hardener to the *INTER-SKIM* at a ratio of 50:1 and mix thoroughly until color is uniform. Working time for this product is approximately 5 minutes.
- Application:** Using a plastic spreader, apply the mixed *INTER-SKIM* to the repair area. The fill should not exceed 1/8" in thickness. Allow to cure for approximately 15 to 20 minutes.
- Finish:** After curing, sand with 180 grit sand paper and then finish sanding with 220 to 400 grit prior to priming or sealing. Refer to paint manufacturers instructions before top coating.

NOTE: Do not apply *INTER-SKIM Polyester Glazing Putty* over the top of Methyl Methacrylate Adhesives.



Product # 8801
32 oz. (946 ml) bottle
Packaged 8 per case

Also available separately:

Product # 8802
Hardener 1 oz. tube
Package Qty: 1