



Conform Tape™ PREMIUM Double Sided Acrylic Foam Tape (Gray - 3/64" Thick)

APPLICATIONS:

- High Strength Acrylic Re-positional Adhesive
- Closed Cell Acrylic Foam For Clean Cutting
- Isolates And Dampens Vibration And Shock
- Maintains Adhesion At Sub-Zero Temperatures
- Conforms To Irregular Substrates

Body Side Mouldings

Accessories

Emblems

Garnish Mouldings

Rocker Panel Mouldings

Interior Trim Panels

	<u>Prod #</u>	<u>Size</u>
	70879	1/4" x 54 ft.
AVAILABLE	70888	3/8" x 54 ft.
SIZES:	70880	1/2" x 54 ft.
	70885	5/8" x 54 ft.
	70887	3/4" x 54 ft.
	70890	1" x 54 ft.

SEE REVERSE SIDE FOR DIRECTIONS AND TECHNICAL INFORMATION

Conform Tape™

PREMIUM Double-Sided Acrylic Foam Tape

NOTE: Installation Temperature: 55°F to 100°F

DIRECTIONS:

1. Remove the old tape from the part and the vehicle. We recommend using IES #7043 Superaser Wheel.
2. Clean the part and the vehicle with IES #1700 or IES # 4700 Super Cleaning Solvent to ensure a film-free surface.
3. All Bodyside Mouldings are not made from the same materials and may require IES #70778 MTP-1 Moulding Tape Primer to promote adhesion. Please refer to the Application Chart to the right. Apply primer if needed.
4. Apply IES Conform Tape™ to the part with the release paper still attached to the tape. Firmly and evenly press the tape on to the part. Be sure you have total contact of the tape and the part.
5. Remove the release paper from the tape, align part and firmly press the part onto the vehicle, making sure pressure has been applied to 100% of the part.

Prod #	Size
70879	1/4" x 54 ft.
70888	3/8" x 54 ft.
70880	1/2" x 54 ft.
70885	5/8" x 54 ft.
70887	3/4" x 54 ft.
70890	1" x 54 ft.
70778	MTP-1 Moulding Tape Primer

APPLICATION CHART		
Substrate Material	Approx. Surface Energy	Primer (for Substrate)
Aluminum	1100	Not Needed
Stainless Steel	1000	Not Needed
Copper	970	Not Needed
Zinc	750	Not Needed
Tin	530	Not Needed
Lead	450	Not Needed
Anodized Aluminum	425	Not Needed
Glass	400	Not Needed
Painted Metal	200	Not Needed
Kapton (Dupont®)	50	May Need Primer
Nylon	48	May Need Primer
Epoxy Paint	47	May Need Primer
Alkyd Enamel	46	May Need Primer
Polyester	45	May Need Primer
Polychloroprene	44	May Need Primer
Polyurethane	42	May Need Primer
Polycarbonate	41	Primer Needed
Polyvinyl Chloride PVC	41	Primer Needed
ABS	39	Primer Needed
Noryl (GE®)	39	Primer Needed
Acrylic	38	Primer Needed
Polyvinyl Acetate	37	Primer Needed
Polystyrene	37	Primer Needed
Ethylene Vinyl Acetate (EVA)	33	Primer Needed
Polyethylene	33	Primer Needed
Polypropylene	30	Primer Needed
EPDM	25	Do Not Use Tape
Tedlar (Dupont®)	22	Do Not Use Tape
Silicone	20	Do Not Use Tape
Teflon (Dupont®)	18	Do Not Use Tape

NOTICE TO PURCHASER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties expressed or implied. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for their intended use and user assumes all risk and liability whatsoever in connection therewith.