

# Safety Data Sheet

Issue Date: 06-Jun-2006

Revision Date: 28-Mar-2014

Version 1

## 1. IDENTIFICATION

### Product Identifier

**Product Name** 8455/8655 Inter-Foam 10 sec Rigid Foam Side A

### Other means of identification

**SDS #** IES-FO8455A

### Recommended use of the chemical and restrictions on use

**Recommended Use** Expandable Foam.

### Details of the supplier of the safety data sheet

#### **Supplier Address**

International Epoxies & Sealers  
30241 Commerce Drive  
San Antonio, FL 33576

### Emergency Telephone Number

**Company Phone Number** 1-800-451-7206

**Emergency Telephone (24 hr)** INFOTRAC 1-352-323-3500 (International)  
1-800-535-5053 (North America)

## 2. HAZARDS IDENTIFICATION

**Appearance** Light yellow to brown  
viscous liquid

**Physical State** Viscous liquid

**Odor** Pungent

### Classification

Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2

### Signal Word

**Danger**

### Hazard Statements

Harmful if inhaled  
Causes skin irritation  
Causes serious eye irritation  
May cause allergy or asthma symptoms or breathing difficulties if inhaled  
May cause an allergic skin reaction  
May cause respiratory irritation  
May cause damage to organs through prolonged or repeated exposure

**Precautionary Statements - Prevention**

Use only outdoors or in a well-ventilated area  
 Wash face, hands and any exposed skin thoroughly after handling  
 Wear protective gloves/protective clothing/eye protection/face protection  
 In case of inadequate ventilation wear respiratory protection  
 Contaminated work clothing should not be allowed out of the workplace  
 Do not breathe dust/fume/gas/mist/vapors/spray

**Precautionary Statements - Response**

Get medical advice/attention if you feel unwell  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Get medical attention  
 IF ON SKIN: Wash with plenty of soap and water  
 Take off contaminated clothing and wash it before reuse  
 If skin irritation or rash occurs: Get medical advice/attention  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician

**Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed  
 Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other Hazards**

Toxic to aquatic life with long lasting effects

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Diphenylmethane, Diisocyanate, isomers, and homologues	9016-87-9	50-60
4,4'Diphenylmethane Diisocyanate (MDI)	101-68-8	30-35
2,2,4-Trimethyl-1,3-pentanediol diisobutyrate	6846-50-0	10-15
Methylenediphenyl diisocyanate	26447-40-5	1-10

\*\*If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

### 4. FIRST-AID MEASURES

**First Aid Measures****General Advice**

Provide this SDS to medical personnel for treatment.

---

<b>Eye Contact</b>	Flush eyes with plenty of water for at least 15 minutes. Materials containing MDI may react with the moisture of the eye forming a thick material which may be difficult to wash from the eyes. Seek medical attention.
<b>Skin Contact</b>	Wash off in flowing warm water or shower with soap. Remove and wash contaminated clothing and discard contaminated shoes. If redness, itching or a burning sensation develops or persists after the area is washed, consult a physician.
<b>Inhalation</b>	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility immediately.
<b>Ingestion</b>	If swallowed, drink 1 or 2 glasses of water or milk. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Seek medical attention.

**Most important symptoms and effects**

<b>Symptoms</b>	Coughing, dryness of throat, headache, nausea, difficult breathing and a feeling of tightness in the chest. Skin contact may result in allergic skin reactions or respiratory sensitization. Watering or discomfort of the eyes. Irritation and corrosive burns to mouth, throat, and stomach. See Section 11: Toxicological Information of this SDS for more detailed symptoms.
-----------------	--

**Indication of any immediate medical attention and special treatment needed**

<b>Notes to Physician</b>	<p>EYES: Stain for evidence of corneal injury. If cornea is burned, instill antibiotic steroid preparation frequently. Workplace vapors have produced reversible corneal epithelial edema impairing vision.</p> <p>SKIN: This compound is a known skin sensitizer. Treat symptomatically as for contact dermatitis or thermal burns. If burned, treat as a thermal burn.</p> <p>INGESTION: Treat symptomatically. There is no specific antidote. Inducing vomiting is contraindicated because of the irritating nature of this compound.</p> <p>INHALATION: Isocyanates are known pulmonary sensitizers. Treatment is essentially symptomatic. An individual having a skin or pulmonary sensitization reaction to this material should be removed from exposure to any isocyanate compound.</p>
---------------------------	---

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Use dry chemical, foam, carbon dioxide or halogenated agents. If water is used, use very large quantities. The reaction between water and hot isocyanate may be vigorous. If possible, contain fire run-off water.

**Unsuitable Extinguishing Media** Not determined.

**Specific Hazards Arising from the Chemical**

Toxic fumes may be given off when material is exposed to fire.

**Hazardous Combustion Products** Toxic gases may be formed by fire. Isocyanate vapor and mist, carbon dioxide, carbon monoxide, nitrogen oxides and traces of hydrogen cyanide.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. At temperatures greater than 400°F, polymeric MDI can polymerize and decompose, which will cause pressure build-up in closed containers. Explosive rupture is possible. Water contamination will produce carbon dioxide. Do not reseal contaminated containers as pressure build-up may rupture the containers. Downwind personnel must be evacuated.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

**Personal Precautions** Evacuate unnecessary personnel. Ensure adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.

**Methods and material for containment and cleaning up**

**Methods for Containment** Prevent further leakage or spillage if safe to do so. Contain and absorb spill immediately. Absorb with appropriate inert material such as sand, clay, etc.

**Methods for Clean-Up** Sweep up absorbed material and shovel into suitable containers for disposal. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations. For waste disposal, see section 13 of the SDS.

Clean Up: The area should then be flushed with a decontamination solution. The decontamination solution is a 5-10% mixture of sodium carbonate and 0.5% liquid detergent in water solution or a 3-8% concentrated ammonium hydroxide and 0.5% liquid detergent in water. Use 10 parts decontamination solution to 1 part spilled material. If the ammonium hydroxide solution is used, ammonia will be evolved as a vapor. Use caution to avoid exposure to high concentrations of ammonia. Allow to stand for 48 hours letting evolved carbon dioxide to escape.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on Safe Handling** Use personal protection recommended in Section 8. Use only with adequate ventilation. Wash face, hands, and any exposed skin thoroughly after handling. In case of inadequate ventilation wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** When stored between 15° and 30°C (60° and 85°F) in sealed containers, typical shelf life is 6 months or more from the date of manufacture. Consult technical data sheet for shelf life requirements affecting performance quality. Should freezing occur, the material must be thawed thoroughly and mixed until uniform. Opened containers must be handled properly to prevent moisture pickup. Store locked up.

**Incompatible Materials** None known based on information supplied.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
4,4-Diphenylmethane Diisocyanate (MDI) 101-68-8	TWA: 0.005 ppm	(vacated) Ceiling: 0.02 ppm regulated under Methylene bisphenyl isocyanate (vacated) Ceiling: 0.2 mg/m <sup>3</sup> regulated under Methylene bisphenyl isocyanate Ceiling: 0.02 ppm Ceiling: 0.2 mg/m <sup>3</sup>	IDLH: 75 mg/m <sup>3</sup> Ceiling: 0.020 ppm 10 min Ceiling: 0.2 mg/m <sup>3</sup> 10 min TWA: 0.005 ppm TWA: 0.05 mg/m <sup>3</sup>
Methylenediphenyl diisocyanate 26447-40-5	-	Ceiling: 0.02 ppm Ceiling: 0.2 mg/m <sup>3</sup>	-

**Appropriate engineering controls****Engineering Controls**

Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS. MDI has a very low vapor pressure at room temperature. General/local ventilation typically control exposure levels very adequate. Uses requiring heating and/or spraying may require more aggressive engineering controls or personal proactive equipment. Monitoring is required to determine engineering controls. An eyewash station shower or other drenching facilities is recommended in the work area.

**Individual protection measures, such as personal protective equipment****Eye/Face Protection**

Chemical splash goggles or safety glasses or full face mask must be used consistent with splash hazard present. If vapor exposure causes eye discomfort, use a full face-piece respirator or supplied air hood.

**Skin and Body Protection**

Wear clothing and gloves impervious to MDI under conditions of use. Materials may include butyl rubber, nitrile rubber, neoprene and Saranax™ coated Tyvek™.

**Respiratory Protection**

A supplied air, full face mask, positive pressure or continuous flow respirator or a supplied air hood is required when airborne concentrations are unknown or exceed threshold values. A positive pressure self-contained breathing apparatus can be used in emergencies or other unusual situations. All equipment must be NIOSH/MSHA approved and maintained. Air purifying (cartridge type) respirators are not approved for protection against isocyanates.

**General Hygiene Considerations**

Avoid contact with skin, eyes and clothing. After handling this product, wash hands before eating, drinking, or smoking. If contact occurs, remove contaminated clothing. If needed, take first aid action shown on section 4 of this SDS. Launder contaminated clothing before reuse.

**9. PHYSICAL AND CHEMICAL PROPERTIES****Information on basic physical and chemical properties**

<b>Physical State</b>	Viscous liquid	<b>Odor</b>	Pungent
<b>Appearance</b>	Light yellow to brown viscous liquid	<b>Odor Threshold</b>	Not determined
<b>Color</b>	Light yellow to brown		
<b><u>Property</u></b>	<b><u>Values</u></b>	<b><u>Remarks • Method</u></b>	
pH	Not determined		
Melting Point/Freezing Point	Not determined		
Boiling Point/Boiling Range	> 204.44 °C / > 400 °F		
Flash Point	> 127.22 / > 261 °F	COC	
Evaporation Rate	Not determined		
Flammability (Solid, Gas)	Not determined		
Upper Flammability Limits	Not determined		
Lower Flammability Limit	Not determined		
Vapor Pressure	Not determined		
Vapor Density	Not determined		
Specific Gravity	> 1.0	@ 25 °C (77 °F)	
Water Solubility	Not soluble		
Solubility in other solvents	Not determined		
Partition Coefficient	Not determined		
Auto-ignition Temperature	Not determined		
Decomposition Temperature	Not determined		
Kinematic Viscosity	Not determined		
Dynamic Viscosity	145-155 cps		
Explosive Properties	Not determined		
Oxidizing Properties	Not determined		

## 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions; Product will react with water.

### Chemical Stability

Stable under recommended storage conditions. Polyisocyanates are highly reactive chemicals.

### Possibility of Hazardous Reactions

None under normal processing.

### Conditions to Avoid

Keep out of reach of children.

### Incompatible Materials

None known based on information supplied.

### Hazardous Decomposition Products

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product Information

<b>Eye Contact</b>	Causes serious eye irritation.
<b>Skin Contact</b>	Causes skin irritation. May cause an allergic skin reaction.
<b>Inhalation</b>	Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation.
<b>Ingestion</b>	Can burn mouth, throat, and stomach.

### Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Diphenylmethane, Diisocyanate, isomers, and homologues 9016-87-9	= 49 g/kg ( Rat )	> 9400 mg/kg ( Rabbit )	= 490 mg/m <sup>3</sup> ( Rat ) 4 h
4,4'Diphenylmethane Diisocyanate (MDI) 101-68-8	= 9200 mg/kg ( Rat )	-	-
2,2,4-Trimethyl-1,3-pentanediol diisobutyrate 6846-50-0	> 3200 mg/kg ( Rat )	-	-
Methylenediphenyl diisocyanate 26447-40-5	> 7400 mg/kg ( Rat )	> 6200 mg/kg ( Rabbit )	= 0.369 mg/L ( Rat ) 4 h

### Information on physical, chemical and toxicological effects

**Symptoms**

INHALATION: At room temperature, MDI vapors are minimal due to low vapor pressure. However, heating, spraying, foaming or otherwise mechanically dispersing (drumming, venting or pumping) operations may generate vapor or aerosol concentrations sufficient to cause irritation or other adverse effects. Excessive exposure may cause irritation of the eyes, upper respiratory tract and lungs. Severe overexposure may lead to pulmonary edema. May cause respiratory sensitization with asthma-like symptoms in susceptible individuals. MDI concentrations below the exposure guidelines may cause allergic respiratory reactions in individuals already sensitized. Symptoms may include coughing, dryness of throat, headache, nausea, difficult breathing and a feeling of tightness in the chest. Effects may be delayed. Impaired lung function (decreased ventilator capacity) has been associated with overexposure to isocyanates. Persons with known respiratory or allergy problems must not be exposed to this product.

Skin Contact: No irritation is likely to develop following short contact periods with skin. Prolonged or repeated exposure can cause skin irritation, reddening, dermatitis, and in some individuals, sensitization. Skin contact may result in allergic skin reactions or respiratory sensitization, but it is not expected to result in absorption amounts sufficient to cause other adverse effects. May stain skin.

Eye Contact: As a liquid or dust, may cause irritation, inflammation and/or damage to sensitive eye tissue. Symptoms include watering or discomfort of the eyes. Corneal injury is unlikely.

Single dose oral toxicity is considered to be extremely low. Can result in irritation and corrosive action in the mouth, stomach tissue and digestive tract.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Carcinogenicity**

The table below indicates whether each agency has listed any ingredient as a carcinogen. However, the product as a whole has not been tested.

Chemical Name	ACGIH	IARC	NTP	OSHA
Diphenylmethane, Diisocyanate, isomers, and homologues 9016-87-9		Group 3		
4,4'Diphenylmethane Diisocyanate (MDI) 101-68-8		Group 3		
Methylenediphenyl diisocyanate 26447-40-5		Group 3		

*IARC (International Agency for Research on Cancer)  
Group 3 IARC components are "not classifiable as human carcinogens"*

**STOT - single exposure** May cause respiratory irritation.

**STOT - repeated exposure** May cause damage to organs through prolonged or repeated exposure.

**Chronic toxicity**

As a result of repeated overexposures or a single large dose, certain individuals develop isocyanate sensitization (chemical asthma) or tissue injury in the upper respiratory tract. Animal tests indicate skin contact alone may also lead to allergic respiratory reaction. These effects may be permanent. Any person developing asthmatic reaction or other sensitization should be removed from further exposure.

**Numerical measures of toxicity**

Not determined

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Toxic to aquatic life with long lasting effects.

### Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
2,2,4-Trimethyl-1,3-pentaned iol diisobutyrate 6846-50-0		1.55: 96 h Pimephales promelas mg/L LC50 static		1.46: 48 h Daphnia magna mg/L EC50
Methylenediphenyl diisocyanate 26447-40-5	3230: 96 h Skeletonema costatum mg/L EC50			1000: 24 h Daphnia magna mg/L EC50

### Persistence/Degradability

Not determined.

### Bioaccumulation

Not determined.

### Mobility

Chemical Name	Partition Coefficient
Methylenediphenyl diisocyanate 26447-40-5	4.5

### Other Adverse Effects

Not determined

## 13. DISPOSAL CONSIDERATIONS

### Waste Treatment Methods

#### **Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

#### **Contaminated Packaging**

Drums/containers must be thoroughly drained to process or storage vessels before removal to an appropriate area for subsequent decontamination. Drums/ containers must be decontaminated in properly ventilated areas by personnel protected from the inhalation of isocyanate vapors. Spray or pour 1 to 5 gallons of decontaminating solution into a drum, making sure the walls are well rinsed. Let the drum/container soak unsealed for 48 hours. Pour out the decontaminating solution and triple rinse the empty container. Puncture or otherwise destroy the rinsed container before disposal. DO NOT heat or cut empty containers with electric or gas torch.

## 14. TRANSPORT INFORMATION

### Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

### DOT

Not regulated

### IATA

Not regulated



**IMDG**

**Marine Pollutant**

This material may meet the definition of a marine pollutant

**15. REGULATORY INFORMATION**

**International Inventories**

**TSCA** Listed

**Legend:**

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List*
- EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*
- ENCS - Japan Existing and New Chemical Substances*
- IECSC - China Inventory of Existing Chemical Substances*
- KECL - Korean Existing and Evaluated Chemical Substances*
- PICCS - Philippines Inventory of Chemicals and Chemical Substances*

**US Federal Regulations**

**CERCLA**

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
4,4'Diphenylmethane Diisocyanate (MDI) 101-68-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**SARA 311/312 Hazard Categories**

Acute Health Hazard Yes  
 Chronic Health Hazard Yes  
 Reactive Hazard Yes

**SARA 313**

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Diphenylmethane, Diisocyanate, isomers, and homologues - 9016-87-9	9016-87-9	50-60	1.0
4,4'Diphenylmethane Diisocyanate (MDI) - 101-68-8	101-68-8	30-35	1.0
Methylenediphenyl diisocyanate - 26447-40-5	26447-40-5	1-10	1.0

**US State Regulations**

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Diphenylmethane, Diisocyanate, isomers, and homologues 9016-87-9	X		
4,4'Diphenylmethane Diisocyanate (MDI) 101-68-8	X		X
Methylenediphenyl diisocyanate 26447-40-5	X	X	

**16. OTHER INFORMATION**

<b><u>NFPA</u></b>	<b>Health Hazards</b> 2	<b>Flammability</b> 1	<b>Instability</b> 1	<b>Special Hazards</b> Not determined
<b><u>HMIS</u></b>	<b>Health Hazards</b> 2	<b>Flammability</b> 1	<b>Physical Hazards</b> 1	<b>Personal Protection</b> Not determined

Issue Date: 06-Jun-2006  
 Revision Date: 28-Mar-2014  
 Revision Note: New format

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**