

1 Identification

- **Product identifier**
- **Trade name: 1695 INTER-WAX Rustproofing Cavity Coating**
Article number: 1695
- **Application of the substance / the mixture** Anticorrosion additive
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
International Epoxies & Sealers
30241 Commerce Drive
San Antonio, FL 33576
Tel: 1-800-451-7206
- **Information department:** Product safety department.
- **Emergency telephone number:** INFOTRAC: 1-800-535-5053 (North America)
1-352-323-3500 (International)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02

Flammable liquid and vapor.



GHS08

Causes damage to the central nervous system through prolonged or repeated exposure.



GHS09

Toxic to aquatic life with long lasting effects.



GHS07

May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08



GHS09

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Naphtha (petroleum), hydrodesulfurized heavy
Naphtha (petroleum), hydrotreated heavy

- **Hazard statements**

H226 Flammable liquid and vapor. H336
May cause drowsiness or dizziness.

Trade name: 1695 INTER-WAX Rustproofing Cavity Coating

H372 Causes damage to the central nervous system through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P243 Take precautionary measures against static discharge.
P280 Wear protective gloves/protective clothing/eye protection.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 0
Fire = 3
Reactivity = 0

Other hazards

The petroleum naphtha / petroleum distillate / lubricating oil meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with additions.

Dangerous components:

CAS: 64742-82-1 EC number: 919-446-0	Naphtha (petroleum), hydrodesulfurized heavy	25-<50%
CAS: 64742-48-9 EC number: 919-857-5	Naphtha (petroleum), hydrotreated heavy	5-<10%
CAS: 61789-86-4 EINECS: 263-093-9	Calcium Sulfonate	5-<10%

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air or oxygen; call for doctor.

After skin contact:

Immediately rinse with water.
If skin irritation continues, consult a doctor.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor.

Information for doctor:

Most important symptoms and effects, both acute and delayed

Disorientation
Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

Trade name: 1695 INTER-WAX Rustproofing Cavity Coating

- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Sand. Do not use water.
CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**
Water
Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.
- **Additional information** Cool endangered receptacles with water spray.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Avoid contact with skin, eyes and clothes.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**
- **PAC-1:**

CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy	350 mg/m ³
CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy	350 mg/m ³
CAS: 67762-90-7 Polydimethylsiloxane, silicon dioxide reaction product	120 mg/m ³
- **PAC-2:**

CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy	1,800 mg/m ³
CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy	1,800 mg/m ³
CAS: 67762-90-7 Polydimethylsiloxane, silicon dioxide reaction product	1,300 mg/m ³
- **PAC-3:**

CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy	40,000 mg/m ³
CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy	40,000 mg/m ³
CAS: 67762-90-7 Polydimethylsiloxane, silicon dioxide reaction product	7,900 mg/m ³

Trade name: 1695 INTER-WAX Rustproofing Cavity Coating

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Use only in well ventilated areas.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges. Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.



Filter A

- **Protection of hands:**



Protective gloves

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.12 mm
- **Penetration time of glove material**
> 480 min.
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Trade name: 1695 INTER-WAX Rustproofing Cavity Coating

· Eye protection:



Tightly sealed goggles

· Body protection: Use protective suit.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Fluid
Color:	Beige
Odor:	Characteristic
Odor threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	145 °C

· Flash point: >30 °C (DIN 53213)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: >200 °C

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower:	0.6 Vol %
Upper:	7 Vol %

· Vapor pressure at 20 °C: 27 hPa

· Vapour pressure at 50 °C: 15 hPa

· Density at 20 °C: 0.85 g/cm³ (DIN 51757)

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:	Not determined. 30
Kinematic at 20 °C:	s (DIN 53211/4)

· Solvent content:

Organic solvents:	52.8 %
VOC content:	52.79 %

Solids content: 47.2 % (DIN 53216)

· Other information: No further relevant information available.

· VOC (EU): 52.79 %

Trade name: 1695 INTER-WAX Rustproofing Cavity Coating

- **VOC (EU):** 448.7 g/l
- **VOC (US):** 448.7 g/l / 3.74 lb/gal

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**
 - ATE (Acute Toxicity Estimate)**
 - Dermal LD50 >4,991 mg/kg
 - CAS: 64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy**
 - Oral LD50 >15,000 mg/kg (RAT)
 - Dermal LD50 3,400 mg/kg (RABBIT)
 - CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy**
 - Oral LD50 >5,000 mg/kg (RAT)
 - Dermal LD50 >3,000 mg/kg (RAT)
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitizing effect through inhalation is possible with prolonged exposure.
- **Additional toxicological information:**
 - The product shows the following dangers according to internally approved calculation methods for preparations:
 - No further relevant information available.
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)**
 - None of the ingredients is listed.
- **NTP (National Toxicology Program)**
 - None of the ingredients is listed.
- **OSHA-Ca (Occupational Safety & Health Administration)**
 - None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:**
 - CAS: 64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy**
 - EC50/48 h 10-22 mg/l (DAPHNIA MAGNA)

Trade name: 1695 INTER-WAX Rustproofing Cavity Coating

EC50/72 h 4.6-10 mg/l (ALGAE)


EC50/96 h 10-30 mg/L (Fish)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Dispose of as dangerous waste.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR/RID/ADN, IMDG, IATA** UN1139
- **UN proper shipping name**
- **DOT** Coating solution
- **ADR/RID/ADN** 1139 Coating solution, ENVIRONMENTALLY HAZARDOUS
- **IMDG** COATING SOLUTION (TURPENTINE SUBSTITUTE),
MARINE POLLUTANT
COATING SOLUTION
- **IATA**
- **Transport hazard class(es)**
- **DOT**
-  A red diamond-shaped hazard label with a flame icon in the center and the text 'FLAMMABLE LIQUID' around the perimeter.
- **Class** 3 Flammable liquids
- **Label** 3

Trade name: 1695 INTER-WAX Rustproofing Cavity Coating

· ADR/RID/ADN, IMDG



· Class 3 Flammable liquids
· Label 3

· IATA



· Class 3 Flammable liquids
· Label 3

· Packing group

· DOT, ADR/RID/ADN, IMDG, IATA III

· Environmental hazards: Product contains environmentally hazardous substances:
Naphtha (petroleum), hydrodesulfurized heavy

· Marine pollutant: Yes
Symbol (fish and tree)
Symbol (fish and tree)

· Special marking (ADR/RID/ADN):

· Special precautions for user Warning: Flammable liquids

· Danger code (Kemler): 30

· EMS Number: F-E, S-E

· Stowage Category A

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information: Transport classification ADR/IMDG is based on packaging
>30ltr(IMDG), <450ltr(ADR).
For other packaging untis different classification can apply.

· DOT

· Quantity limitations On passenger aircraft/rail: 60 L
On cargo aircraft only: 220 L

· ADR/RID/ADN

· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· IMDG

· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 1139 COATING SOLUTION, 3, III, ENVIRONMENTALLY HAZARDOUS

Trade name: 1695 INTER-WAX Rustproofing Cavity Coating

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

· **TSCA new (21st Century Act) (Substances not listed)**

CAS: 61789-86-4 | Calcium Sulfonate

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02

GHS07

GHS08

GHS09

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Naphtha (petroleum), hydrodesulfurized heavy

Naphtha (petroleum), hydrotreated heavy

· **Hazard statements**

H226 Flammable liquid and vapor.

H336 May cause drowsiness or dizziness.

H372 Causes damage to the central nervous system through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/protective clothing/eye protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

**Safety Data Sheet acc.
to OSHA HCS**

Printing date 09/27/2018

Reviewed on 03/20/2018

Trade name: 1695 INTER-WAX Rustproofing Cavity Coating

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

- **Water hazard class:** Water hazard class 3 (Self-assessment): extremely hazardous for water.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product safety department.

· **Contact:** mail@useies.com

· **Date of preparation / last revision** 09/27/2018 / 10

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2