

INTEGRA-GRAY - SALAMI-PACK MS POLYMERIC SEAM SEALER CAULKING GUN GRADE

A permanently flexible, non-sag, MS-polymeric seam sealer formulated to duplicate OEM brush lines and beaded seams. Paintable and has excellent adhesion to bare metal, properly primed metals, SMC, fiberglass & most plastics. Contains no isocyanates.

BENEFITS

- Duplicates O.E.M. Seams
- Paintable Immediately
- Excellent Adhesion
- Permanently Flexible
- Non-Sag
- No Shrinking
- Isocyanate Free
- Low VOC's
- Holds Brush Lines
- UV Resistant
- Non-yellowing
- Environmental Friendly

TECHNICAL DATA

| | |
|--------------------------------|--------------------------------------|
| Tack Free Time: | Less than one hour @77°F / 50%RH |
| Skin Time: | 30-40 minutes @77°F / 50%RH |
| Sag: | Non-sagging |
| Cure Rate: | 1/8" per 24 hours @77°F / 50%RH |
| Tensile Strength | 300 psi |
| Elongation at Break | 200% |
| High Temp Resistance | Up to 300°F for short periods |
| Low Temp Flexibility | Properties retained to -75°F |
| Shore A Hardness | 45 - 50 |
| Modulus at 100% | 200 psi |
| Joint Movement (per ASTM C719) | +/- 25% |
| UV Ratings | Excellent UV and moisture resistance |
| Corrosive Properties: | Non-corrosive |
| Staining: | Non-staining |
| Shelf Life | 12 months from date of purchase |

CAUTION

For professional use only. Before using this or any IES product, refer to the Safety Data Sheet (SDS) and label for safe use and handling instructions.



DIRECTIONS

1. Surface should be clean, dry and free of dirt, grease and oil. Sealer can be applied to bare metal, primed or painted surfaces. Surface should be scuffed.
2. Cut off end of the foil package and insert into the IES #96208 gun.
3. Attach plastic nozzle and retaining ring to the gun. Cut nozzle to the desired shape and size.
4. Apply sealer to seam as needed.
5. If feathering is desired, smooth with a putty knife or stick.
6. Remove excess sealer immediately.
7. If painting, paint per manufacturers recommendations immediately or within four days.

NOTE: Some cleaners/solvents/coatings & paints may not be compatible with this product and should be tested by the user before proceeding with intended repair procedure.

STORAGE

Product should be stored in a cool, dry location in unopened containers at a temperature between 50°F to 85°F (10°C to 30°C) unless otherwise labeled. Protect package from direct sunlight and heat. Do not handle or store near open flame or other sources.

COMPETITIVE PRODUCTS

3M 8370 (salami-pack)

PRODUCT AVAILABLE

| | | |
|-------|-------------------------|------------|
| 1570P | 10.1 fl. oz. foil pouch | 6 per case |
| 1571 | Replacement Tips | 6 per case |

NOTICE TO PURCHASER: The following warranty is in lieu of all other expressed or implied warranties, specifically all goods are manufactured of first class materials and by competent professionals. We have no control over the use and application of our products. Our liability shall not exceed the purchase price.