

RUBBERIZED UNDERCOAT (Solvent Based)

A premium quality, rubber based undercoating with outstanding adhesion and abrasion resistance. Dries quickly and is tack free. Exceptionally tough and highly flexible. Use on undercarriage, doors, trunks and fenders. Good texture and is paintable with no bleed-through. Seals and protects. Sound Deadens. Prevents rust. Will not chip, crack or peel.

BENEFITS

- Seals and protects
- Sound deadener
- Rust preventative
- Superior salt corrosion protection
- Dries to the touch in less than 30 minutes
- Paintable!
- Contains no asphalt!
- 50 State Compliant

APPLICATIONS

- All automotive types
- Can be used as a protective coating for metal applications
- Autobody Interiors/Underhood/Underbody

PROPERTIES

Appearance	Opaque
Color	Black
Odor	Solvent
Flash Point:	-15.6 to 10°C (3.9 to 14°F)
Specific Gravity:	1.379
Weight Per Gallon	11.51 lbs/gal
Water Solubility	Practically insoluble
VOC Content (%)	24.72
VOC -Lbs Per Gal	2.84

CAUTION

For professional use only. Before using this or any IES product, refer to the Safety Data Sheet (SDS) and label for safe use and handling instructions.



PAINTABLE
FAST DRYING
SEALS AND PROTECTS-
PREVENTS RUST
DEADENS SOUND

DIRECTIONS

1. Stir thoroughly before using. Protect areas not to be painted from overspray.
2. Clean surfaces to be coated with IES Super Cleaning Solvent.
3. Apply with IES #1670 Siphon Gun using air pressure of 40-60 psi.
4. Allow to dry before painting with top coat.
5. After use, thoroughly clean gun.

PRODUCT AVAILABLE

1600	32 fl. oz. Can	6 per case
1601	1 Gallon Can	1 per case

Also Available

1604	Empty 32 oz. can	6 per case
-------------	------------------	------------

NOTICE TO PURCHASER: The following warranty is in lieu of all other expressed or implied warranties, specifically all goods are manufactured of first class materials and by competent professionals. We have no control over the use and application of our products. Our liability shall not exceed the purchase price.