

#4205 JAMB-IT Clear

A fast drying lacquer based spray paint that provides durable indoor and outdoor protection. Resistant to the effects of weather and many chemicals. Resists abrasion and heat (250F). Bare surfaces or rusted metal surfaces should first be primed with our IES primers to ensure proper adhesion.

SUGGESTED USES:

- Automotive
- Industrial
- Marine
- Construction
- Home

PHYSICAL PROPERTIES:

| | |
|-------------------------|--|
| Flash point | -40 F |
| Specific Gravity | 0.86 |
| Solids Content | Glosses: ~15% Flats: ~15% Metallics: ~13% |
| MIR value | Glosses: ~1.25, cannot exceed 1.40 Clear: ~1.43, cannot exceed 1.50 Metallics: ~1.60, cannot exceed 1.90 |
| HAPs content | Glosses: ~13% Clear: ~25% Metallics: ~30% |
| Storage Temperature | 40-100F |
| Application Temperature | 50-90F |
| Durability | Good |
| Abrasion Resistance | Good |
| Gasoline Resistance | No |
| Heat Resistance | 2500 F |
| Resin System | Acrylic lacquer |
| Shelf life | Guaranteed for 2 years |



**Fast Drying
Exceptional Clarity
Excellent Gloss**

DRY TIME:

| | |
|-----------|------------|
| Tack free | 5 minutes |
| To recoat | 20 minutes |

*At 720 F, 50% humidity, 1.5 mil thickness

Curing/Recoat time is extended with multiple coats and excessively thick coats

| | |
|---------|---|
| Gloss*: | High Gloss, >80 Semi-Gloss, 10-20 Flat, <15 |
|---------|---|

*as measured on a 600 gloss meter

PRODUCT

#4205 JAMB-IT Clear 20 oz Aerosol 12/Box

NOTICE TO PURCHASER: The following warranty is in lieu of all other expressed or implied warranties, specifically all goods are manufactured of first class materials and by competent professionals. We have no control over the use and application of our products. Our liability shall not exceed the purchase price.

International Epoxies & Sealers | P.O. Box 185 San Antonio, FL 33576 USA | Toll Free: (800) 451-7206