

SPRAY GREASE WHITE LITHIUM

A heavy-bodied, multipurpose lithium based lubricant used to lubricate hinges, latches, window regulators, cables and other metal to metal contact parts. Heat resistant. Excellent corrosion resistance. Will not wash off. Will not run or drip.

APPLICATION AND USES

Door and hinges, door stop latches, door striker plates, power radio antennas, speedometer cables, window mechanisms, hood and trunk compartment springs, seat regulators, wiper mechanisms, ash tray channel guides, brake parts, seat tracks, distributor cams, etc. Machinery and tools, chains, slides, cams, etc. Linkages, cables, gears, pulleys, couplings, winches, hitches, trailer rollers. Implements, tractors, machinery, chains, conveyors, etc. Overhead garage door channels, fans, air conditioners, sliding doors and windows, garden and lawn equipment, tools, toys, etc.

FEATURES

Will not run or drip.
Excellent water and heat resistance.
Excellent corrosion inhibitor.
Extension tube included.

BENEFITS

Heat resistant.
Excellent protection against dirt, dust.
Withstands strong weather conditions.

PRODUCT SPECIFICATIONS

NLGI Grade	2
Soap Type	Lithium
Appearance	Off White/Viscous
Worked Penetration, ASTM D 217, 77°F, 60 strokes	265 - 295
Dropping Point, ASTM D 2265, °F Min.	365+
Rust & Corrosion, ASTM D 1743	Pass
4-Ball EP,kg	315
4-Ball Wear, ASTM D 2266, OK Load, Min.	<.60
Base Oil Viscosity	
cSt @ 100°C	9.5 - 11
cSt @ 40°C	145 - 195
Viscosity Index	60
Working Temperature	-30 to 300°F



DIRECTIONS

1. Shake well before spraying.
2. Hold can 6-8 inches from the surface to be sprayed.
3. Wipe off excess with a clean rag.

STORAGE

Product should be stored in a cool, dry location in unopened containers at a temperature between 50°F to 85°F (10°C to 30°C) unless otherwise labeled. Protect package from direct sunlight and heat. To prevent contamination of unused material, do not return any material to its original container.

PRODUCT AVAILABLE

4505	16 oz. Size Aerosol	12/bx
	Net Weight 12 oz.	

NOTICE TO PURCHASER: The following warranty is in lieu of all other expressed or implied warranties, specifically all goods are manufactured of first class materials and by competent professionals. We have no control over the use and application of our products. Our liability shall not exceed the purchase price.