

#4509 FAST DRYING RUBBERIZED UNDERCOAT

A premium quality, rubber based undercoating with outstanding adhesion and abrasion resistance. Dries quickly and is tack free. Seals and protects. Sound Deadens. Prevents rust. Exceptionally tough and highly flexible. Use on undercarriage, doors, trunks and fenders. Good texture and is paintable with no bleed-through. Exhibits unique leveling qualities that aid in achieving a smooth, uniform surface. Will not chip, crack or peel.

BENEFITS

Seals and protects
Sound deadener
Rust preventative
Superior salt corrosion protection
Dries to the touch in less than 30 minutes

APPLICATIONS

All automotive types
Panel & Fender Undersides
Hoods & Decks
Trunk Interiors
Rust Holes
All Chassis Parts
Can be used as a protective coating for metal applications

TECHNICAL DATA

Flammability	"Extremely Flammable"
Solids Content	~60%
VOC Content (%)	~39%, cannot exceed 40%
Storage Temperature	40°F - 90°F
Application Temperature	50°F - 100°F
Durability	Very Good
Abrasion Resistance	Very Good
Heat Resistance	300°F
Gasoline Resistance	No
Resin System	Petroleum Asphalt
Dry Time* (@72°F, 50% humidity, 1.5 mil thickness)	To touch - 10 minutes To handle - 6 hours

* Curing/recoat time is extended with multiple coats and excessively thick coats



**FAST DRYING
PAINTABLE
HIGH SOLIDS
SEALS AND PROTECTS-
PREVENTS RUST**

DIRECTIONS

1. Surface must be clean, dry and free of all loose contaminants. Protect surrounding areas from spray mist. For best results, use when can is between 50°F and 90°F (10°C and 32°C).
2. Shake can well before using. Ensure the agitator ball moves freely. Reshake intermittently during use.
3. Spray surface with steady, even strokes at a distance of 8-10 inches from surface.
4. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. DO NOT stick pin or other objects into can opening. With can and sprayhead pointing away from you, reinsert sprayhead with a gentle twisting motion.
5. To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Completely empty can may be recycled or disposed of with regular trash. Dispose of empty cans responsibly. DO NOT incinerate or compact.

PRODUCT AVAILABLE

4509 24 oz. Aerosol Can 12 per case
Net Weight 19.4 oz.

NOTICE TO PURCHASER: The following warranty is in lieu of all other expressed or implied warranties, specifically all goods are manufactured of first class materials and by competent professionals. We have no control over the use and application of our products. Our liability shall not exceed the purchase price.