

TRIM MASKING TAPE

This is a premium quality tape for masking of rubber parts. It allows paint to flow under the molding. The tape is easy to handle and quick in application. Its high flexibility and adhesion, combined with moisture absorbing crepe backing ensures perfect paint results.

RECOMMENDED USES

Masking rubber around flush fitted car windows
Masking rubber around sun roofs
Masking gaps between body parts

APPLICATION

Temperature between 50°F and 120°F
Surface must be clean and free from dust and grease.
Avoid touching exposed adhesive surface of the tape as this impairs the performance.
Pressure sensitive adhesive must be applied with maximum pressure in order to achieve maximum adhesion.
The maximum level of performance will be reached after bonding
period of 24 hours @ 74°F (23°C).

CAUTION

For professional use only. Before using this or any IES product, refer to the Safety Data Sheet (SDS) and label for safe use and handling instructions.

STORAGE

Should be stored in a clean, dry and well ventilated location between 50°F to 86°F (10°C to 30°C).



PROPERTIES

Adhesive	Rubber Adhesive
Adhesion	4.5 N/cm
Tensile Strength	41 N/cm
Elongation	11%
Service temperature range	-30°F -> + 212°F
Solvent resistance	Good
Moisture resistance	Good
Pet Film	10 mm
Carrier	Slightly creped paper with PET-film enforced Glassine paper
	Thickness: 0.19 mm
	Size 50 mm x 10 m (10mm plastic strip)

Part #70740

PRODUCT AVAILABLE

70740 50mm x 10m 4 per case

NOTICE TO PURCHASER: The following warranty is in lieu of all other expressed or implied warranties, specifically all goods are manufactured of first class materials and by competent professionals. We have no control over the use and application of our products. Our liability shall not exceed the purchase price.