

TRIM MASKING TAPE

High-Temp, Acrylic

70741 HIGH-TEMP, ACRYLIC ADHESIVE

A washi paper masking tape, with high adhesive properties, especially designed to perform well in most industrial painting and automotive masking applications. A high temperature tape where excellent holding and high temperature performance are required.

RECOMMENDED USES

Use with solvent and water based paints
Suitable for most painting and drying applications
Suitable for both industrial and automotive applications
Good adhesion on all kinds of substrates
Excellent for outside applications and rough surfaces

APPLICATION

Temperature between 60°F and 86°F (15°C and 30°C).
Surface must be clean and free from dust and grease.
Avoid touching exposed adhesive surface of the tape as this impairs the performance.
Pressure sensitive adhesive must be applied with maximum pressure in order to achieve maximum adhesion.
The maximum level of performance will be reached after bonding period of 24 hours @ 74°F (23°C).

CAUTION

For professional use only. Before using this or any IES product, refer to the Safety Data Sheet (SDS) and label for safe use and handling instructions.

STORAGE

Should be stored in a clean, dry and well ventilated location between 50°F to 86°F (10°C to 30°C).



PROPERTIES

Adhesive	Acrylic
Carrier	Washi paper
Color	Light blue
Total thickness	0.114 mm/114 µm (Micron) 4.48mil
Adhesive strength	5.9 N/25 mm
Tensile strength	114,9 N/25 mm
Elongation	9.3%
Temp resistance	up to +120°C/248°F (60 min)
Solvent resistance	Good
Moisture resistance	Good
UV resistance	3-6 months
Part #70741	50mm x 10m (10mm plastic strip)

PRODUCT AVAILABLE

70741 50mm x 10m, High-Temp 4 per case