

BSR Tape

(Buzz - Squeak - Rattle)

High density felt-like material designed for use on interior trim panels, dash boards, consoles and other various areas where buzzing, squeaks, rattles and chirps occur. High-strength acrylic adhesive keeps tape in place.



APPLICATIONS

Any area where squeaks, chirps and rattles occur. Interior trim panels, dash boards, consoles, instrument panels, etc. Also referred to as anti-squeak tape or squeak reduction tape.

BENEFITS

Reduces friction
Eliminates squeaks, chirps and rattles
Noise reduction
Abrasion resistance

PROPERTIES

Color: Black
Thickness: 1mm
Application temperature: 60°F Minimum

High Strength Acrylic Adhesive

High Density Material

Eliminates Squeaks and Rattles

Rolls and Sheets To Fit Any Application

Easy to apply!

DIRECTIONS

1. Make sure the application area is clean and free of any contaminates.
2. Remove release liner and firmly press tape into place.

STORAGE

Product should be stored in a cool, dry location in unopened containers at a temperature between 50°F to 85°F (10°C to 30°C) unless otherwise labeled. Protect package from direct sunlight and heat.

PRODUCT AVAILABLE

70762	2" x 12 ft. Roll	1/box
70764	12" x 12" sheet	2/box

These suggestions and data are based on information we believe to be reliable and accurate, but no guarantee of their accuracy is made. International Epoxyes & Sealers shall not be liable for any damage, loss or injury, direct or consequential arising out of the use or the inability to use the product. In every case, we urge and recommend that purchasers, before using any product in full scale production, make their own tests to determine whether the product is of satisfactory quality and suitability for their operations, and the user assumes all risk and liability whatsoever, in connection therewith.